


RETRACTORS



THE PERFECT RETRACTING CLEANING SYSTEM

- **Ultra Hygienic Design**
- **Complete Flush Retraction**
- **Fast Effective Wash**
- **Variable Cleaning Heads**
- **Reduced Contamination**
- **Smooth Seal Inside Vessel**
- **Reduced Cleaning/Down Time**
- **Flexible Application Design**

Versatile & Unique

The MR1 and MR2 range of retractors offer a unique and highly valuable method of cleaning vessels, pipe work and ducting where a cleaning head can not remain in situ when the process is running. The units sit externally to the process system and extend under the power of the cleaning fluid into the appropriate section of the vessel to be cleaned when required. After performing the cleaning operation they either auto retract or can be manually retracted with compressed air, CO₂, Nitrogen or other gas. The wide variety of cleaning head options provides a unit that can be designed into most systems and provide full cleaning solutions.

Applications

The MR1 and MR2 units are ideal for installing into ducting and pipe work where the flow through the production system needs to remain free from obstructions. They are equally suited to be used in larger vessels where there are agitators and mixing systems which would have their mechanical action impeded by cleaning heads fitted in situ. The units are suitable for use in process systems running under a vacuum. The units are compact in design and effective in performance. They meet all the essential FDA material requirements and are also available in ATEX exempt form. This makes the units highly suitable for the pharmaceutical, biotech, food, beverage and other hygiene conscious industries.

Operation

Wash fluid enters a drive chamber causing the unit to extend into its cleaning position. The cleaning head (depending on the model chosen) then rotates and produces a fast moving spray of powerful high energy droplets providing instant coverage of the target area. The specially designed cleaning pattern ensures the high energy droplets use the minimum amount of wash fluid to deliver optimum performance. Units are usually used in pairs or multiples to ensure no blind spot areas are created.

BRECONCHERRY
SELLERSCLEAN

RETRACTORS

BRECONCHERRY SELLERSCLEAN

International specialists in the design and
manufacture of tank cleaning equipment

Australia & New Zealand Distributor:



TECHNICAL PROJECTS

DNZ OF MATHI PRODUCTS PTY. LTD A.B.N. 83 090 115 478

4/44 Carrington Road
Castle Hill NSW 2154
Australia

Tel: +61 (0)2 9634 3370
Fax: +61 (0)2 9634 6418
Email: sales@tecpro.com.au
Web: www.tecpro.com.au



We reserve the right to change specification
without notice. Whilst we endeavour to provide
accurate up to date information, all information
is provided as a guide only.

“Breconcherry”, “Retractors” are internationally
registered trade marks of Breconcherry Limited.
Copyright © Breconcherry Limited 1999

Maintenance & Inspection

The low wear design requires minimal maintenance. Any spare parts, technical assistance or repair facilities required can be obtained through the global Breconcherry distributor network. As with all mechanical devices, it is recommended that the unit be regularly inspected for correct operation.

Minimum Manhole/Flange Size

The minimum flange connection size required for the unit will depend on the type of model chosen. Typical tri clamp flange connections of 2.5” and 3”, but custom sizes can also be supplied.

Technical Data

Materials of Construction:	Stainless Steel 316/316L, PTFE, C-PTFE, PEEK, Hastelloy
Max. Operating Temperature:	100° Centigrade
Max. Ambient Temperature:	140° Centigrade
Standard Connections:	Tri Clamp
Nozzle Characteristics:	Custom Spray Pattern depending on cleaning head chosen



For optimal efficiency use a pre-filter or strainer to prevent particulate clogging.

BRECONCHERRY
SELLERSCLEAN

WWW.TECPRO.COM.AU